

**DC COMPONENTS CO., LTD.**

RECTIFIER SPECIALISTS

M1
THRU
M7**TECHNICAL SPECIFICATIONS OF SURFACE MOUNT SILICON RECTIFIER****VOLTAGE RANGE 50 to 1000 Volts****CURRENT 1.0 Ampere****FEATURES**

- * Ideal for surface mounted applications
- * Low leakage current

**SMA(DO-214AC)****MECHANICAL DATA**


- * Case: Molded plastic
- * Epoxy: UL 94V-0 rate flame retardant
- * Terminals: Solder plated, solderable per MIL-STD-750, Method 2026
- * Polarity: As marked
- * Mounting position: Any
- * Weight: 0.064 gram

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%.



Dimensions in inches and (millimeters)

	SYMBOL	M1	M2	M3	M4	M5	M6	M7	UNITS
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS Voltage	V _{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage	V _{DC}	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Current at TA = 75°C	I _o				1.0				Amps
Peak Forward Surge Current I _{FM} (surge): 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	I _{FSM}				30				Amps
Maximum Forward Voltage at 1.0A DC	V _F				1.1				Volts
Maximum DC Reverse Current at	IR	@ TA = 25°C			5.0				uAmps
Rated DC Blocking Voltage			@ TA = 125°C		50				
Maximum Reverse Recovery Time (Note 3)	t _{rr}				2.5				uSec
Typical Thermal Resistance (Note 2)	R _{θJL}				30				°C/W
Typical Junction Capacitance (Note 1)	C _J				15				pF
Operating and Storage Temperature Range	T _J , T _{STG}				-65 to + 175				°C

NOTES : 1. Measured at 1.0 MHz and applied reverse voltage of 4.0VDC

2. Thermal Resistance (Junction to Ambient), .24in²(6.0mm²) copper pads to each terminal.

3. Test Conditions: IF=0.5A, IR=1.0A, IRR=0.25A.

RATING AND CHARACTERISTIC CURVES (M1 thru M7)

FIG. 1 - TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 2 - MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 4 - TYPICAL REVERSE CHARACTERISTICS





FIG. 5 - TYPICAL JUNCTION CAPACITANCE



DC COMPONENTS CO., LTD.